

BESANTEK Audio Impedance Tester is designed for true measurement of speaker system actual impedance at 1kHz.

Features:

- Large LCD: 68 x 34mm (2.677" x 1.338").
- True measurement of speaker systems actual impedance at 1kHz.
- Three test ranges allow testing of home theater and commercial sound systems.
- Measures transformer impedances.
- Battery operation.
- Low battery warning indicator.
- Data hold function.
- 0Ω adjustment.
- Accessories: Instruction manual, test leads, soft pouch and batteries.



BST-AIT01

Technical Specification:

BST-AIT01

Measuring Ranges	0-20Ω/0-200Ω/0-2kΩ
Test Frequency	1kHz
Accuracy	20Ω: $\pm 2\%rdg \pm 2dgt$ or $\pm 0.1\Omega$, which is greater 200Ω/2kΩ: $\pm 2\%rdg \pm 2dgt$
Low Battery Indication	" $\text{[} \ominus \text{]}$ " symbol appears on the display
Data Hold Indication	" [HOLD] " symbol appears on the display
Display	LCD 3½ digit (2000 counts)
Power Source	1.5V (AA) x 8
Dimensions	175 (L) x 85 (W) x 75 (D) mm
Weight	Approx. 620g (battery included)

Accessories



Ordering Information:

- BST-AIT01: Audio Impedance Tester.

Vendas:

JBM INSTRUMENTOS LTDA.
 Rua Araguaia, nº 69 - Boa Vista
 Santa Rita do Sapucaí - MG
 CEP: 37540-000
 Tel : +55 (35) 3471-3014 / (35) 3471-3711
 E-mail: vendas@jbminstrumentos.com.br
 Web: www.jbminstrumentos.com.br